

## 精密用スプリング Bタイプ

注番	線径	外径	密着長	自由長	初張力	バネ定数	1ℓ'ツ	価格
B - 1	0.4	4.0	4	12	0.058	0.0643	20	2000
B - 2	"	"	8	16	"	0.0285	"	2000
B - 3	"	"	10	18	"	0.0223	"	2000
B - 4	"	"	20	28	"	0.0107	"	2000
B - 5	"	4.5	4	13	0.045	0.0435	"	2000
B - 6	"	"	8	17	"	0.0193	"	2000
B - 7	"	"	10	19	"	0.0151	"	2000
B - 8	"	"	20	29	"	0.0072	"	2000
B - 9	"	"	30	39	"	0.0047	"	2000
B - 10	"	5.0	4	14	0.036	0.0308	"	2000
B - 11	"	"	8	18	"	0.0136	"	2000
B - 12	"	"	10	20	"	0.0107	"	2000
B - 13	"	"	20	30	"	0.0051	"	2000
B - 14	"	"	30	40	"	0.0033	"	2000
B - 15	"	5.5	4	15	0.029	0.0226	"	2000
B - 16	"	"	8	19	"	0.0100	"	2000
B - 17	"	"	10	21	"	0.0078	"	2000
B - 18	"	"	20	31	"	0.0037	"	2000
B - 19	"	"	30	41	"	0.0024	"	2000
B - 20	"	6.0	4	16	0.0240	0.0170	"	2000
B - 21	"	"	8	20	"	0.0075	"	2000
B - 22	"	"	10	22	"	0.0059	"	2000
B - 23	"	"	20	32	"	0.0028	"	2000
B - 24	"	"	30	42	"	0.0018	"	2000
B - 25	"	"	40	52	"	0.0013	"	2000
B - 26	0.5	4.0	4.5	23	0.096	0.1074	"	2000
B - 27	"	"	9	17	"	0.0477	"	2000
B - 28	"	"	14	22	"	0.0306	"	2000
B - 29	"	"	18	26	"	0.0226	"	2000
B - 30	"	4.5	4.5	14	0.074	0.0723	"	2000
B - 31	"	"	9	18	"	0.0321	"	2000
B - 32	"	"	14	23	"	0.0206	"	2000
B - 33	"	"	18	27	"	0.0152	"	2000
B - 34	"	"	27	36	"	0.0099	"	2000
B - 35	"	5.0	4.5	15	0.058	0.0510	"	2000
B - 36	"	"	9	19	"	0.0226	"	2000

注番	線径	外径	密着長	自由長	初張力	バネ定数	1ℓ'ツ	価格
B - 37	0.5	5.0	14	24	0.058	0.0145	20	2000
B - 38	"	"	18	28	"	0.0107	"	2000
B - 39	"	"	27	37	"	0.0070	"	2000
B - 40	"	5.5	4.5	16	0.047	0.0373	"	2000
B - 41	"	"	9	20	"	0.0165	"	2000
B - 42	"	"	14	25	"	0.0106	"	2000
B - 43	"	"	18	29	"	0.0078	"	2000
B - 44	"	"	27	38	"	0.0051	"	2000
B - 45	"	6.0	4.5	17	0.039	0.0281	"	2000
B - 46	"	"	9	21	"	0.0124	"	2000
B - 47	"	"	14	26	"	0.0080	"	2000
B - 48	"	"	18	30	"	0.0059	"	2000
B - 49	"	"	27	39	"	0.0038	"	2000
B - 50	"	"	36	48	"	0.0028	"	2000
B - 51	0.5	4.0	10	18	0.15	0.0759	"	2000
B - 52	"	"	15	23	"	0.0488	"	2000
B - 53	"	"	20	28	"	0.0359	"	2000
B - 54	"	"	25	33	"	0.0284	"	2000
B - 55	"	"	30	38	"	0.0235	"	2000
B - 56	"	4.5	10	19	0.1150	0.0508	"	2000
B - 57	"	"	15	24	"	0.0326	"	2000
B - 58	"	"	20	29	"	0.0240	"	2000
B - 59	"	"	25	34	"	0.0190	"	2000
B - 60	"	"	30	39	"	0.0157	"	2000
B - 61	"	5.0	10	20	0.091	0.0357	"	2000
B - 62	"	"	15	25	"	0.0229	"	2000
B - 63	"	"	20	30	"	0.0169	"	2000
B - 64	"	"	25	35	"	0.0133	"	2000
B - 65	"	"	30	40	"	0.0110	"	2000
B - 66	"	5.5	20	31	0.074	0.0123	"	2000
B - 67	"	"	30	41	"	0.0080	"	2000
B - 68	"	"	40	51	"	0.0060	"	2000
B - 69	"	6.0	10	22	0.061	0.0195	"	2000
B - 70	"	"	15	27	"	0.0125	"	2000
B - 71	"	"	20	32	"	0.0092	"	2000
B - 72	"	"	25	37	"	0.0073	"	2000

## 精密用スプリング Bタイプ

注番	線径	外径	密着長	自由長	初張力	バネ定数	1ℓの	価格
B-73	0.5	6.0	30	42	0.061	0.0060	20	2000
B-74	0.5	6.5	10	23	0.051	0.0150	20	2000
B-75	0.5	6.5	20	33	0.051	0.0071	20	2000
B-76	0.5	6.5	30	43	0.051	0.0046	20	2000
B-77	0.5	6.5	35	48	0.051	0.0039	20	2000
B-78	0.5	6.5	40	53	0.051	0.0034	20	2000
B-79	0.5	7.0	10	24	0.044	0.0118	20	2000
B-80	0.5	7.0	15	29	0.044	0.0076	20	2000
B-81	0.5	7.0	20	34	0.044	0.0056	20	2000
B-82	0.5	7.0	25	39	0.044	0.0044	20	2000
B-83	0.5	7.0	30	44	0.044	0.0036	20	2000
B-84	0.5	7.0	35	49	0.044	0.0031	20	2000
B-85	0.5	7.0	40	54	0.044	0.0027	20	2000
B-86	0.5	8.0	20	36	0.033	0.0037	20	2000
B-87	0.5	8.0	25	41	0.033	0.0028	20	2000
B-88	0.5	8.0	30	46	0.033	0.0023	20	2000
B-89	0.5	8.0	35	51	0.033	0.0020	20	2000
B-90	0.5	8.0	40	56	0.033	0.0017	20	2000
B-91	0.5	8.5	20	37	0.029	0.0030	10	1600
B-92	0.5	8.5	25	42	0.029	0.0023	10	1600
B-93	0.5	8.5	30	47	0.029	0.0019	10	1600
B-94	0.5	8.5	35	52	0.029	0.0016	10	1600
B-95	0.5	8.5	40	57	0.029	0.0014	10	1600
B-96	0.5	9.0	20	38	0.025	0.0025	10	1600
B-97	0.5	9.0	25	43	0.025	0.0019	10	1600
B-98	0.5	9.0	30	48	0.025	0.0016	10	1600
B-99	0.5	9.0	35	53	0.025	0.0014	10	1600
B-100	0.5	9.0	40	58	0.025	0.0012	10	1600
B-101	0.6	5.0	6	16	0.197	0.1782	10	1600
B-102	0.6	5.0	12	22	0.197	0.0792	10	1600
B-103	0.6	5.0	18	28	0.197	0.0509	10	1600
B-104	0.6	5.0	30	40	0.197	0.0297	5	1600
B-105	0.6	5.5	6	17	0.159	0.1290	10	1600
B-106	0.6	5.5	12	23	0.159	0.0573	10	1600
B-107	0.6	5.5	18	29	0.159	0.0368	10	1600
B-108	0.6	5.5	30	41	0.159	0.0215	5	1600

注番	線径	外径	密着長	自由長	初張力	バネ定数	1ℓの	価格
B-109	0.6	6.0	6	18	0.131	0.0964	10	1600
B-110	0.6	6.0	12	24	0.131	0.0428	10	1600
B-111	0.6	6.0	18	30	0.131	0.0275	10	1600
B-112	0.6	6.0	30	42	0.131	0.016	5	1600
B-113	0.6	7.0	12	26	0.093	0.0257	10	1600
B-114	0.6	7.0	18	32	0.093	0.0165	10	1600
B-115	0.6	7.0	30	44	0.093	0.0096	5	1600
B-116	0.6	8.0	12	28	0.07	0.0166	10	1600
B-117	0.6	8.0	18	34	0.07	0.0107	10	1600
B-118	0.6	8.0	30	46	0.07	0.0062	5	1600
B-119	0.6	9.0	12	30	0.054	0.0113	10	1600
B-120	0.6	9.0	18	36	0.054	0.0073	10	1600
B-121	0.6	9.0	30	48	0.054	0.0042	5	1600
B-122	0.7	6.0	7	19	0.252	0.1889	10	1600
B-123	0.7	6.0	14	26	0.252	0.0839	10	1600
B-124	0.7	6.0	28	40	0.252	0.0397	10	1600
B-125	0.7	6.0	35	47	0.252	0.0314	5	1600
B-126	0.8	6.0	8	20	0.446	0.3413	10	1600
B-127	0.8	6.0	16	28	0.446	0.1517	10	1600
B-128	0.8	6.0	24	36	0.446	0.0975	10	1600
B-129	0.8	6.0	40	52	0.446	0.0568	5	1600
B-130	0.8	7.0	8	22	0.314	0.2014	10	1600
B-131	0.8	7.0	16	30	0.314	0.0895	10	1600
B-132	0.8	7.0	24	38	0.314	0.0575	10	1600
B-133	0.8	7.0	40	54	0.314	0.0335	5	1600
B-134	0.8	8.0	8	24	0.233	0.1286	10	1600
B-135	0.8	8.0	16	32	0.233	0.0571	10	1600
B-136	0.8	8.0	24	40	0.233	0.0367	10	1600
B-137	0.8	8.0	40	56	0.233	0.0214	5	1600
B-138	0.8	9.0	16	34	0.179	0.0386	10	1600
B-139	0.8	9.0	24	42	0.179	0.0248	10	1600
B-140	0.8	9.0	40	58	0.179	0.0145	5	1600
B-141	1.0	8.0	10	26	0.601	0.3416	10	1600
B-142	1.0	8.0	20	36	0.601	0.1518	10	1600
B-143	1.0	8.0	30	46	0.601	0.0976	10	1600
B-144	1.0	8.0	40	56	0.601	0.0719	5	1600

