

精密用ロングスプリングHタイプ

注番	線径	外径	密着長	自由長	バネ定数	価格
H3-1	0.3	3.0	100	106	0.0514	480
H3-2	0.3	4.0	100	108	0.0141	480
H4-1	0.4	3.0	100	106	0.2648	480
H4-2	0.4	4.0	300	308	0.0686	450
H4-3	0.4	5.0	300	308	0.0250	450
H4-4	0.4	6.0	300	312	0.0112	525
H5-1	0.5	5.0	300	310	0.0857	435
H5-2	0.5	6.0	300	312	0.0376	480
H5-3	0.5	7.0	300	314	0.0190	490
H6-1	0.6	5.0	300	310	0.2402	480
H6-2	0.6	6.0	300	312	0.1029	490
H6-3	0.6	7.0	300	314	0.0511	590
H6-4	0.6	8.0	300	316	0.0282	490
H7-1	0.7	5.0	300	310	0.5872	450
H7-2	0.7	7.0	300	314	0.1200	450
H8-1	0.8	6.0	300	312	0.5296	480
H8-2	0.8	8.0	300	316	0.1372	550
H8-3	0.8	10.0	300	320	0.0500	550
H8-4	0.8	12.0	300	324	0.0224	680
H9-1	0.9	7.0	300	314	0.5003	590
H9-2	0.9	9.0	300	318	0.1543	590
H9-3	0.9	11.0	300	322	0.0623	675
H9-4	0.9	13.0	300	326	0.0298	675
H9-5	0.9	15.0	300	330	0.0160	715
H10-1	1.0	8.0	300	316	0.4860	690
H10-2	1.0	10.0	300	320	0.1715	715
H10-3	1.0	12.0	300	324	0.0751	715
H10-4	1.0	14.0	300	328	0.0379	715
H10-5	1.0	16.0	300	332	0.0212	715
H12-1	1.2	8.0	300	316	1.4131	590
H12-2	1.2	10.0	300	320	0.4804	590
H12-3	1.2	12.0	300	324	0.2058	620
H12-4	1.2	15.0	300	330	0.0751	715
H12-5	1.2	18.0	300	336	0.0336	715
H14-1	1.4	10.0	300	320	1.1744	620
H14-2	1.4	12.0	300	324	0.4908	715

注番	線径	外径	密着長	自由長	バネ定数	価格
H14-3	1.4	15.0	300	330	0.1753	715
H14-4	1.4	17.0	300	334	0.0998	730
H14-5	1.4	20.0	300	340	0.0486	840
H14-6	1.4	23.0	300	346	0.0265	840
H15-1	1.5	10.0	300	320	1.7665	715
H15-2	1.5	12.0	300	324	0.7289	715
H15-3	1.5	14.0	300	328	0.3535	730
H15-4	1.5	16.0	300	332	0.1916	730
H16-1	1.6	10.0	300	320	2.6017	725
H16-2	1.6	12.0	300	324	1.0593	725
H16-3	1.6	14.0	300	328	0.5092	840
H16-4	1.6	16.0	300	332	0.2743	840
H16-5	1.6	18.0	300	336	0.1606	840
H16-6	1.6	20.0	300	340	0.1002	870
H18-1	1.8	13.0	300	326	1.4308	840
H18-2	1.8	15.0	300	330	0.7207	1040
H18-3	1.8	17.0	300	334	0.4015	1135
H18-4	1.8	20.0	300	340	0.1911	1165
H20-1	2.0	15.0	300	330	1.3241	970
H20-2	2.0	18.0	300	336	0.558	980
H20-3	2.0	20.0	300	340	0.3429	1065
H20-4	2.0	25.0	300	350	0.1252	1065
H20-5	2.0	30.0	300	360	0.0560	1080
H23-1	2.3	15.0	300	330	3.0213	970
H23-2	2.3	20.0	300	340	0.7537	980
H23-3	2.3	25.0	300	350	0.2697	1080
H23-4	2.3	30.0	300	360	0.1192	1165
H23-5	2.3	35.0	300	370	0.0606	1180
H25-1	2.5	15.0	300	330	5.0000	970
H25-2	2.5	20.0	300	340	1.2148	980
H25-3	2.5	25.0	300	350	0.4287	1010
H25-4	2.5	30.0	300	360	0.1878	1135
H30-1	3.0	20.0	300	340	3.5329	1180
H30-2	3.0	25.0	300	350	1.2011	1180
H30-3	3.0	30.0	300	360	0.5144	1430
H30-4	3.0	35.0	300	370	0.2557	1765

